

Box Sash Window Specification Guide

Traditional Box Sash Windows with cords and weights from our New Build Range have been tested for compliance with current Building Regulations including Part Q which requires a mandatory pass of PAS 24 enhanced security performance requirements suitable for dwellings for doorsets and windows in the UK. This is your guarantee that the product you are purchasing is being monitored by a UKAS accredited certification body to ensure compliance.

Manufacturer:	Scotts of Thrapston
Range:	New Build
Product:	Box Sash Window
Timber:	Engineered Red Grandis
Frame Depth:	162mm
External Liner:	102mm
Mullion:	140mm standard
Options:	98mm slim 198 double
Counter Balance:	Lead Weights
Cill:	162 x 74mm
Cill Projection:	Flush
Options	35mm 60mm 85mm
Cill Horns:	Required/Not Required
External liner:	Square
Options:	Bead Mould
Sash horns:	Required /Not Required
Finish:	Scotts White
Options:	RAL Colour Colour Match Dual Finish

Glazing Bars:	21mm
Options	18mm
Profile:	Ovolo
Options:	Lambs Tongue Chamfered
Double Glass Units:	24mm comprising - 4mm tough: 16mm Argon: 4mm tough low E 24.8mm comprising - 4mm tough: 14mm Argon: 6.8mm tough low E
Window U Value:	1.3w/m2K
Unit Spacer Bar:	White
Options	Black
Ironmongery:	Sash Catch, Sash Pulley, Sash Lift, Sash Lock (from Scotts Traditional Suite)
Ironmongery Finish:	Brass (from Scotts Traditional Suite)
Options:	From Scotts Traditional Suite
Trickle Vents:	Required/Not Required
Child Restrictor:	Required/Not Required

The New Build Range Box Sash Window from Scotts of Thrapston has been tested in accordance with BS 6375

