

Flush Faced Casement Window Specification Guide

Traditional Flush Faced Casement Windows from our New Build Range have been tested for compliance with current Building Regulations including Part Q which requires a mandatory pass of PAS 24 enhanced security performance requirements suitable for dwellings for door sets and windows in the UK. This is your guarantee that the product you are purchasing is being monitored by a UKAS accredited certification body to ensure compliance.

Manufacturer:	Scotts of Thrapston
Range:	New Build
Product:	Flush Faced Casement Window
Timber:	Engineered Red Grandis
Frame Head:	68 x 93mm
Frame Jamb:	57 x 93mm
Mullion:	68mm
Option:	90mm 114mm
Cill:	68mm x 93mm
Option:	90mm
Cill Projection:	60mm
Option:	35mm 85mm 110mm 140mm
Sashes:	64mm
Option:	57mm slim
Cill Horns:	Required / Not Required
Hinges:	Concealed Friction Hinges easy clean 60 degree opening
Option:	Egress Hinge 90 degree opening with easy clean function
Finish:	Scotts White
Options:	RAL Colour Colour Match Dual Finish
Glazing Method:	Scotts of Thrapston Applied Bar Internally Glazed System

Glazing Bars:	21mm
Options	18mm
Profile:	Ovolo
Options:	Lambs Tongue Chamfered
Double Glass Units:	24mm comprising - 4mm tough: 16mm Argon: 4mm tough low E 24.8mm comprising - 4mm tough: 14mm Argon: 6.8mm tough low E
Window U Value:	1.3w/m2K
Unit Spacer Bar:	White
Options	Black
Ironmongery:	Standard Locking Handle (from Scotts Hardex Suite)
Option	From Scotts Traditional Suite From Scotts Armor Coat Suite
Ironmongery Finish:	Brass (From Scotts Hardex Suite)
Options:	From Scotts Traditional Suite From Scotts Armor Coat Suite
Trickle Vents:	Required/Not Required
Child Restrictor:	Required/Not Required
Performance:	Tested in accordance with BS 6375

