

## Box Sash Window Specification Guide

Traditional Box Sash Windows with cords and weights from our New Build Range have been tested for compliance with current Building Regulations including Part Q which requires a mandatory pass of PAS 24 enhanced security performance requirements suitable for dwellings for doorsets and windows in the UK. This is your guarantee that the product you are purchasing is being monitored by a UKAS accredited certification body to ensure compliance.

<b>Manufacturer:</b>	<b>Scotts of Thrapston</b>
<b>Range:</b>	New Build
<b>Product:</b>	Box Sash Window
<b>Timber:</b>	Engineered/Solid Hardwood
<b>Frame Depth:</b>	162mm
<b>External Liner:</b>	102mm
<b>Mullion:</b>	140mm standard 98mm slim
<b>Options:</b>	198 double Lead Weights
<b>Counter Balance:</b>	162 x 74mm
<b>Cill:</b>	Flush
<b>Cill Projection:</b>	
<b>Options</b>	35mm 60mm 85mm
<b>Cill Horns:</b>	Required/Not Required
<b>External liner:</b>	Square
<b>Options:</b>	Bead Mould
<b>Sash horns:</b>	Required /Not Required
<b>Finish:</b>	Scotts White
<b>Options:</b>	RAL Colour Colour Match Dual Finish

<b>Glazing Bars:</b>	21mm
Options	18mm
<b>Profile:</b>	Ovolo
Options:	Lambs Tongue Chamfered
<b>Double Glass Units:</b>	24mm comprising - 4mm tough: 16mm Argon: 4mm tough low E 24.8mm comprising - 4mm tough: 14mm Argon: 6.8mm tough low E
<b>Window U Value:</b>	1.3w/m2K
<b>Unit Spacer Bar:</b>	White
Options	Black
<b>Ironmongery:</b>	Sash Catch, Sash Pulley, Sash Lift, Sash Lock (from Scotts Traditional Suite)
<b>Ironmongery Finish:</b>	Brass (from Scotts Traditional Suite)
Options:	From Scotts Traditional Suite
<b>Trickle Vents:</b>	Required/Not Required
<b>Child Restrictor:</b>	Required/Not Required

The New Build Range Box Sash Window from Scotts of Thrapston has been tested in accordance with BS 6375

