

Flush Faced Casement Window Specification Guide

Manufacturer:	Scotts of Thrapston
Range:	Refurbishment Range
Product:	Flush Faced Casement Window
Timber:	Engineered/Solid Hardwood
Frame Head:	57 x 93mm
Option:	68mm (mandatory for trickle vent)
Frame Jambs:	57mm
Option:	68mm
Frame Mullion:	68mm
Option:	90mm
Frame Transom:	68mm
Option:	90mm
Cill:	68mm
Option	90mm
Cill Projection:	60mm
Option	35mm
	85mm
	110mm
	140mm
Cill Horns:	Required / Not Required
Hinges:	Traditional Butt Hinges
Option:	Concealed Friction Hinges
Finish:	Scotts White
Options:	RAL Colour
	Colour Match
	Dual Finish
Glazing Method:	Scotts of Thrapston Applied Bar Internally Glazed System
Glazing Bars:	21mm
Options	18mm

Profile: Ovolo

Options: Lambs Tongue
Chamfered

Double Glass Units: 16mm comprising - 4mm tough: 8mm Krypton: 4mm tough low E

Window U Value: 1.6w/m2K

Unit Spacer Bar: White

Options Black

Locking Mechanism: Multipoint Espagnolette

Option: Single point locking (no warranty)
Hung only (no warranty)

Ironmongery: Standard Locking Handle (Scotts Hardex Suite)

Option From Scotts Traditional Suite
From Scotts Armor Coat Suite

Ironmongery Finish: Brass

Options: From Scotts Hardex Suite
From Scotts Traditional Suite
From Scotts Armor Coat Suite

Trickle Vents: Required/Not Required

Child Restrictor: Required/Not Required

